

Product Name
ALACO Retractable Wall Ladders

Manufacturer
ALACO Ladder Co.
5167 G Street, Chino, CA 91710-5143
Phone: (888) 310-7040 Fax: (909) 591-7565
E-mail:sales@alacoladder.com Web Site: www.alacoladder.com

Product Description

BASIC USE

Model 660 retractable ladders are designed for space-saving interior access to roof hatches from small rooms. They are ideal for restaurants, tool storage rooms, workshops and mini-warehouses.

CONSTRUCTION & MATERIALS

ALACO aluminum ladders and their components are fabricated from 6061-T6 aluminum alloy for added safety, strength and long-lasting durability, with no painting required. Model 660 aluminum ladders feature of 1-1/8" (29mm) thick round serrated rungs, secured with cast aluminum connectors and 4 solid rivets. They are equipped with 4 (or 6) retractable mounting bracket assemblies for flat storage against the wall. Non-marking solid rubber feet extend 3/4" (19.1mm) from the rail ends. Rubber plugs extend 3/4" (19.1mm) from the side rail tops to provide closed end protection.

TYPE

Retractable Fixed Wall Ladders- Model 660 Roof hatch access

SIZES

Height- up to 17'-3" (5.26 m)
Width- 18-1/4" (463.6 mm)

FINISHES & COATINGS

Mill finish is standard on aluminum ladders.
Factory applied paint coatings and chem-film treatment for field applied primers are available upon request.
Custom coatings and surface treatments are also offered.

Technical Data

APPLICABLE STANDARDS

American National Standards Institute (ANSI) - ANSI A14.3 American National Standard for Ladders - Fixed - Safety Requirements

APPROVALS

U.S. Occupational Safety and Health Administration (OSHA)
ALACO aluminum ladders are certified to meet OSHA/ANSI A14.3 standards for fixed wall

ladders.

ENVIRONMENTAL CONSIDERATIONS

Metals used in these products are presumed to be recyclable upon demolition.

PHYSICAL/CHEMICAL PROPERTIES

Additional material and product information and performance data are available to design professionals upon request.

Installation

PREPARATORY WORK

Handle and store product according to ALACO recommendations.

METHODS

Model 660 Retractable Aluminum Ladders Standard Assembly

Provide backing in wall that is consistent with bracket locations. Prepunched brackets are templates for fastener locations. Request bracket locations, if needed.

Complete installation recommendations for all product models are available from the manufacturer.

BUILDING CODES

Building code requirements and product compliance data can be obtained from the manufacturer. Installation must comply with applicable local, state and national code jurisdictions.

Availability & Cost

AVAILABILITY

Contact manufacturer for information on product availability.

COST

Budget pricing and installed cost information may be obtained from the manufacturer.

Warranty

ALACO ladders carry a limited warranty of 5 years.

Maintenance

ALACO ladders are maintenance-free, with no painting required.

Technical Services

A staff of factory trained service personnel offers design assistance and technical support. ALACO Ladder Co. offers shop drawings, guide specifications and design consultation.

Filing Systems

Additional product information is available from the manufacturer upon request.